



LED FLOODLIGHT (PF0.95)

****<<ULTRA SERIES>>****



APPLICATION

- Ideal for Parking Areas, Stadium, Gardens, Billboard, Pathway, Facade Lighting, and All Commercial or Residential Areas.



FEATURES

- High Brightness and Long Life LED Chips.
- Operating Temperature -20° C ~ 50° C.
- Solid Aluminium Die-Casting and Textured Glass Material Diffuser.
- Build-In With Pressure Release Valve.
- Heavy Duty and High Energy Efficiency Design.



**10 KV
SURGE
PROTECTION**



MODEL	POWER (W)	CCT (K)	LUMEN (LM)	SIZE L x W x H (MM)	NET WEIGHT (KG)	PACKING (/CTN)
BSFL-8100-1/ULT	100W	6500	15000	290 x 214 x 47	1.7	10
BSFL-8150-1/ULT	150W	6500	22500	320 x 260 x 55	2.4	5
BSFL-8200-1/ULT	200W	6500	30000	372 x 267 x 55	3.2	5
BSFL-8300-1/ULT	300W	6500	45000	432 x 318 x 55	4.6	4
BSFL-8400-1/ULT	400W	6500	60000	353 x 457 x 56	5.0	3
BSFL-8500-1/ULT	500W	6500	75000	391 x 507 x 60	5.6	2

