



LED FLOOD LIGHT

****<< EVOLUTION SERIES>>****



APPLICATION

- Ideal for Parking Areas, Gardens, Billboard, Facade Lightings, and All Commercial or Residential Areas.



FEATURES

- High Brightness and Long Life LED Chips (25,000Hrs).
- Operating Temperature -20° C ~ 50° C.
- Aluminium Die-Casting and Polycarbonate Material Diffuser.
- No External Driver Required (DOB) and High Energy Efficiency.



MODEL	POWER (W)	CCT (K)	LUMEN (LM)	POWER FACTOR (PF)	SIZE L x W x H (MM)	NET WEIGHT (KG)	PACKING (/CTN)
BSFL-8030/EVL	30W	6500	3300	>0.5	136 x 181 x 26	0.2	20
BSFL-8050/EVL	50W	6500	5500	>0.5	158 x 201 x 27	0.4	20
BSFL-8100/EVL	100W	6500	11000	>0.9	209 x 254 x 27	0.7	20
BSFL-8150/EVL	150W	6500	16500	>0.9	248 x 327 x 30	1.0	10
BSFL-8200/EVL	200W	6500	22000	>0.9	291 x 387 x 31	1.4	5
BSFL-8300/EVL	300W	6500	33000	>0.9	327 x 453 x 33	1.8	5

