

LED SOLAR FLOOD LIGHT WITH MONOCRYSTALLINE SILICON SOLAR PANEL

APPLICATION

- Ideal for Parking Areas, Stadiums, Pathway, Garden and All Commercial and Residential Areas.

FEATURES

- Easy To Install and No Complicated Wiring Required.
- High Brightness and Long Life LED Chips.
- Solar Charging with LED Light Indicator.
- Solar Charging time 6±2 Hours.
- Working Time 12 Hours (Full Charge AUTO Mode).
- DC 3.2V (LiFePO4) Battery.
- Installation height : 150W(2-4m) / 300W(3-5m) / 500W(4-6m)
- Solid Aluminium Die-Casting Housing and Polycarbonate Material Diffuser.
- Intelligent Power Saving Design and Come with Remote Control (Manually ON/OFF, Brightness Level and Turn Off Timer).
- Solar Cable Length: 4 meter



MODEL	SYSTEM WATTAGE (W)	CCT (K)	LUMEN (LM)	BATTERY CAPACITY (V/AH)	SOLAR POWER (V/W)	SOLAR PANEL SIZE L x W x H (MM)	LAMP BODY SIZE L x W x H (MM)	NET WEIGHT (KG)	PACKING (/CTN)
BSSLFL-1150	150W	3000/6500	1800	3.2/15	6/20	350 x 350 x 17	171 x 205 x 44	2.3	8
BSSLFL-1300	300W	6500	3600	3.2/25	6/30	350 x 530 x 17	209 x 267 x 44	3.2	6
BSSLFL-1500	500W	6500	6000	3.2/35	6/40	350 x 700 x 17	250 x 330 x 44	4.5	4

