


💡

RECESSED T-BAR PRISMATIC
DIFFUSED FITTING (METRIC SIZE)

- 📄
- APPLICATION
 - Mainly Used for General Lighting in Office, Hypermarket, Hospital, Complex.



🎯

FEATURES

TYPE	T-Bar Prismatic Diffused Fitting (Metric Size)
MODEL/CODE	BSC/MM
BODY	High Quality Gauge Sheet Steel
PAINT WORK	Fully Couated With Epoxy Powder Coated Finished
MOUNTING	Recessed Type
LIGHT SOURCE	Fluorescent TLD Lamp and T8 LED Tube
LAMP HOLDER & STARTERHOLDER	Polycarbonate Material
COMPONENT	Conventional or Electronic Ballast, EL Emergency Power Pack , Fused Terminal Block

MODEL	DESCRIPTION	L (mm)	L1 (mm)	W (mm)	H (mm)
BSC 220/MM (1' x 2')	2 TUBE (1 x 2 feet)	612	585	295	92
BSC 220/MM	2 TUBE (2 x 2 feet)	612	585	595	92
BSC 320/MM	3 TUBE (2 x 2 feet)	612	585	595	92
BSC 420/MM	4 TUBE (2 x 2 feet)	612	585	595	92
BSC 240/MM (1' x 4')	2 TUBE (1 x 4 feet)	1222	1195	295	92
BSC 240/MM	2 TUBE (2 x 4 feet)	1222	1195	595	92
BSC 340/MM	3 TUBE (2 x 4 feet)	1222	1195	595	92
BSC 440/MM	4 TUBE (2 x 4 feet)	1222	1195	595	92