



LED MODULE FLOODLIGHT MOSO LED DRIVER

****<<ECO SERIES>>****



APPLICATION

- Ideal for Parking Areas, Stadiums, Courtyard, Storefront, Stations, Wharf Bridge, Warehouse, All Commercial and Residential Area.



FEATURES

- High Brightness and Long Life LED Chips (40,000Hrs)
- Operating temperature -10° C ~ 50° C.
- Solid Aluminium Die-Casting Housing and Polycarbonate Material Diffuser.
- Efficiency : 130lm/W
- Heat Dissipation Performance.
- Free Combination : 200W capable upgrade until 600W
- Aluminium Bracket, Anti-Corrosion Rustproof.
- Heavy Duty and High Energy Efficiency Design



MOSO®



**Using MOSO LED Driver
Highly Reliable & Efficient**

Surge protection: DM: 6KV, CM: 6KV



MODEL	POWER (W)	CCT (K)	LUMEN (LM)	SIZE L x W x H (MM)	QUANTITY OF LED (PCS)	NET WEIGHT (KG)	PACKING (/CTN)
BSFLHD-1200/ECO	200W	6500	26000	260 x 345 x 105	SMD 240	3.1	1
BSFLHD-1300/ECO	300W	6500	39000	370 x 345 x 105	SMD 360	4.2	1
BSFLHD-1400/ECO	400W	6500	52000	470 x 345 x 105	SMD 480	5.6	1
BSFLHD-1500/ECO	500W	6500	65000	580 x 345 x 105	SMD 600	6.6	1

