



LED SOLAR FLOOD LIGHT

****<<ECO SERIES>>****



APPLICATION

- Ideal for Parking Areas, Stadiums, Pathway, Garden and All Commercial and Residential Areas.



FEATURES

- Easy To Install and No Complicated Wiring Required.
- High Brightness and Long Life LED Chips.
- Solar Charging with LED Light Indicator.
- Solar Charging time 6±2 Hours.
- Working Time 12 Hours (Full Charge AUTO Mode).
- DC 3.2V (LiFePO4) Battery.
- Installation height : 120W(3-4m) / 200W(4-5m) / 400W(5-6m) / 600W(6-7m) / 800W(8-9m) / 1000W(9-10m)
- Intelligent Power Saving Design and Come with Remote Control.
- Polycarbonate Material for Body and Diffuser.
- Solar Panel Cable Length : 2 meters.



MODEL	SYSTEM WATTAGE (W)	CCT (K)	LUMEN (LM)	BATTERY CAPACITY (V/AH)	SOLAR POWER (V/W)	SOLAR PANEL SIZE L x W x H (MM)	LAMP BODY SIZE L x W x H (MM)	NET WEIGHT (KG)	PACKING (/CTN)
BSSLFL-120/ECO	120W	6500	2040	3.2/10	6/15	235 x 350 x 17	211 x 191 x 45	1.4	8
BSSLFL-200/ECO	200W	6500	3400	3.2/20	6/25	400 x 350 x 17	257 x 244 x 45	2.7	6
BSSLFL-400/ECO	400W	6500	5100	3.2/30	6/35	600 x 350 x 17	313 x 286 x 46	4.2	4
BSSLFL-600/ECO	600W	6500	6800	3.2/40	6/45	680 x 350 x 17	343 x 315 x 46	4.4	3
BSSLFL-800/ECO	800W	6500	8000	3.2/60	6/60	670 x 535 x 25	443 x 383 x 61	8.0	1
BSSLFL-1000/ECO	1000W	6500	10000	3.2/80	6/80	670 x 640 x 25	443 x 383 x 61	8.1	1

