

SOLAR LED STREET LIGHT
WITH MONOCRYSTALLINE
SILICON SOLAR PANEL

APPLICATION

- Ideal for Parking Areas, Pathway, Garden,
All Commercial and Residential Area.

FEATURES

- Easy to Install and No Complicated Wiring Required
- Operating Temperature -10° C ~ 40° C.
- Solar Charging with LED Light Indicator.
- Solar Charging time 6±2 Hours.
- Working Time 12 Hours (Full Charge AUTO Mode).
- DC 3.2V (LiFePO4) Battery.
- Installation Height: 200W(3-5m) / 400W(4-6m) / 600W(5-7m).
- Cast Iron Material Housing and Polycarbonate Material Diffuser.
- Come with Remote Control (Manually ON/OFF, Brightness Level and Turn Off Timer)
- Pole Width Diameter : 55~60mm



MODEL	SYSTEM WATTAGE (W)	CCT (K)	LUMEN (LM)	BATTERY CAPACITY (V/AH)	SOLAR POWER (V/W)	SOLAR PANEL SIZE L x W x H (MM)	LAMP BODY SIZE L x W x H (MM)	NET WEIGHT (KG)	PACKING (/CTN)
BSSL-1200	200W	6500	2400	3.2/20	6/25	350 x 450 x 17	490 x 215 x 60	3.5	1
BSSL-1400	400W	3000/6500	4800	3.2/30	6/35	350 x 600 x 19	490 x 215 x 60	4.5	1
BSSL-1600	600W	6500	7200	3.2/40	6/45	670 x 445 x 25	700 x 255 x 60	6.4	1

