



💡

T8 IP65 ANTI CORROSIVE FITTING

📋

APPLICATION

- Ideal for Parking Area, Canopy, Loading Bays, Industrial, Production Area, Integrated Transit, Factories, Foundaries and Under Canopy Application.

🎯

FEATURES

- Suitable for Damp & Corrosive Environment.
- Gasket are Injected into Lamp Body to Form Continuous Seal.
- IP65 Degree of Protection against Dust and Water Blasting.
- UV Protected Polycarbonate Diffuser With High Impact Resistance.

MODEL	SIZE Ø (FT)	BASE BODY / DIFFUSER	LED WIRING	SIZE L x W x H (MM)	NET WEIGHT (KG)	PACKING (/CTN)
BCR/ECO/120	1 x 2	Polycarbonate	Normal	665 x 75 x 90	0.6	12
BCR/ECO/220	2 x 2	Polycarbonate	Normal	665 x 110 x 90	0.7	8
BCR/ECO/140	1 x 4	Polycarbonate	Normal	1260 x 75 x 90	0.9	12
BCR/ECO/140/PH	1 x 4	Polycarbonate	Philips	1260 x 75 x 90	0.9	12
BCR/ECO/240	2 x 4	Polycarbonate	Normal	1260 x 110 x 90	1.3	8
BCR/ECO/240/PH	2 x 4	Polycarbonate	Philips	1260 x 110 x 90	1.3	8

