




RECESSED T-BAR PRISMATIC DIFFUSED FITTING (METRIC SIZE)



APPLICATION

- Mainly Used for General Lighting in Office, Hypermarket, Hospital, Complex.



FEATURES

TYPE	T-Bar Prismatic Diffused Fitting (Metric Size)
MODEL/CODE	BSC/MM
BODY	High Quality Gauge Sheet Steel
PAINT WORK	Fully Coured With Epoxy Powder Coated Finished
MOUNTING	Recessed Type
LIGHT SOURCE	T8 LED Tube
LAMP HOLDER	Polycarbonate Material
COMPONENT	EL Emergency Power Pack , Fused Terminal Block

MODEL	DESCRIPTION	L (MM)	L1 (MM)	W (MM)	H (MM)
BSC 220/MM (1' x 2')	2 TUBE (1 x 2 feet)	612	585	295	92
BSC 220/MM	2 TUBE (2 x 2 feet)	612	585	595	92
BSC 320/MM	3 TUBE (2 x 2 feet)	612	585	595	92
BSC 420/MM	4 TUBE (2 x 2 feet)	612	585	595	92
BSC 240/MM (1' x 4')	2 TUBE (1 x 4 feet)	1222	1195	295	92
BSC 240/MM	2 TUBE (2 x 4 feet)	1222	1195	595	92
BSC 340/MM	3 TUBE (2 x 4 feet)	1222	1195	595	92
BSC 440/MM	4 TUBE (2 x 4 feet)	1222	1195	595	92